

RCKMS - Technology



The Thinking Behind RCKMS Software



Build a software suite **based on an open source software, best practices, and standards-based principles**, incorporating the following components:

1. **General-purpose Public Health Decision Support Service (PH-DSS)** for processing ongoing, real-time requests that can determine whether or not a case report should be sent to Public Health based on the medical record information supplied to the service. (The DSS bases these decisions on the executable reporting specifications created in the Authoring Tool)
2. **Easy-to-use Authoring Tool** to assist jurisdictions in conceptualizing, creating, maintaining and deploying machine-executable reporting specifications (for each desired condition) to the DSS service. Authoring tool should be generalizable so it can evolve with authoring requirements *and* runtime environments
3. **Integrated with the Public Health Community Platform (PHCP)**, or option to run on its own

RCKMS Public Health Decision Support Service



- PH-DSS built atop the [OpenCDS](#)
 - Freely available Clinical Decision Support (CDS) software: “multi-institutional, collaborative effort to develop scalable, CDS tools and resources”
 - Facilitate widespread availability of advanced CDS capabilities through collaborative development of **standards-based DSS** infrastructure and tooling
 - **Open Source**
 - Active collaboration by RCKMS team
- Lower barriers to adoption; foster interoperability between public health and other clinical systems
 - [HL7 Decision Support Service Standard](#) for standard functionality and interfaces
 - [HL7 Virtual Medical Record \(vMR\)](#) for consistent modeling of the rules
 - [HL7 Clinical Quality Language \(CQL\)](#) and [Drools](#) as executable representation of rules
 - Evolve to future models and payloads (e.g. FHIR) if needed

Characteristics of the RCKMS PH-DSS




- Web Service architecture
- Scalable by volume of requests and by number of jurisdictions/conditions
- Conducive for future enhancements
 - Accessibility to Authoring Tool data
 - Support of different payloads
- **Evaluates patient data (input)** on a request-by-request basis
 - **Determines** (or requestor may specify) which jurisdictions are relevant based on patient's address, where the patient received care, and/or servicing laboratory
 - Executes the relevant reporting specifications for those jurisdictions
- **Outputs**
 - **Notice of Reportability (NoR)** for *each* jurisdiction
 - Specifies list of conditions reportable to the jurisdiction: for each condition, where to report, and timeframe to submit case report

RCKMS Authoring Tool



- Built atop the [CDS Administration Tool \(“CAT”\)](#)
 - o Open source framework and application for managing CDS logic and deployments
 - o Terminology/concept management, authoring & deployment of rules, and automated test case creation
 - o Includes a web (UI) front end
- Simplifies authoring of reporting specifications
 - o Two user views: RCKMS Administrator view, Jurisdiction view
 - o Reporting specifications data entry simplified via grid format
 - o Generated rules in a standards-based output
 - o Ability to generate a “human-readable” view of any reporting specification

How the Authoring Tool works



1. Jurisdiction enters reporting criteria into authoring interface (website)
- RCKMS tool comes pre-populated with **default reporting criteria** that users can choose to use, or customize to meet their jurisdictional needs
2. Information entered → stored in repository → Linked to decision support service
3. Jurisdiction can test whether criteria entered correctly by using test manager

Preconfigured Defaults for Each Condition (“out-of-the-box”)



- Users may adopt reporting specifications “as is”, or modify them
 - Users may simply accept the default rules for each condition if they wish
 - To modify defaults, select preconfigured “Criteria” to add or remove
 - If additional criteria desired, contact RCKMS team
- If Value Sets change, Authoring Tool and PH-DSS automatically accounts for changes
- If guidelines/logic change, RCKMS team updates Authoring Tool with *new* default rule logic and publishes new default rules; jurisdiction incorporate into local version

Default Reporting Specification (Chlamydia)



Manage Default Logic Sets + Add Logic Set			
Logic Set Properties	Lab Reporting Logic Sets	Provider/Facility Reporting Logic Sets	
	Lab1	Dx	Lab
Reporting Timeframe	1 day(s)	1 day(s)	3 day(s)
Define Default Reporting Specifications			
Clinical			
Chlamydia (i.e., as a Diagnosis or active Problem or mentioned in text as a cause of death or a significant condition contributing to death)		Sufficient	
Death Record			
No criteria of this type			
Demographic			
No criteria of this type			
Epidemiologic			
No criteria of this type			
Laboratory			
All result values for laboratory tests specific for detecting chlamydia species organisms, nucleic acid, or antigen by any method in a clinical specimen (i.e., 'negative' and 'positive' results)			
All result values for laboratory tests specific for detecting chlamydia trachomatis organisms, nucleic acid, or antigen by any method in a clinical specimen (i.e., 'negative' and 'positive' results)			
Isolation of C. trachomatis by culture methods in a clinical specimen	Sufficient		Sufficient
Detection of C. trachomatis antigen by any method in a clinical specimen	Sufficient		Sufficient
Detection of C. trachomatis nucleic acid by any method in a clinical specimen	Sufficient		Sufficient

⏪ ⏩ ⏴ ⏵
Save Apply Cancel

RCKMS Test Cases



- Test reporting specification logic under varying conditions to ensure correct operation
- Automated testing: run all tests at once or individually
- Accepts eICR file imports or manually entered tests
- User enters:
 - Test (sample) patient data inputs
 - Expected outputs:
 - Reportable: Yes/No
 - List of Criteria met
- Outputs:
 - Test pass/fail
 - Conditions that are reportable
 - List of Criteria met

Test Case Editor



RCKMS Test Case Editor - [Save Option 3]

Details | Jurisdiction and Criteria Details | Test Case Results

ID: 702c7510883491ee4d9410661ab1b405

Skip?

Name: Default > Pertussis > Lab Reporter > Criteria > Reportable Positive > Expected = Yes > Criteria: Isolation of Bordetella pertussis virus by culture methods in a clinical specimen

Description: Default > Pertussis > Lab Reporter > Criteria > Reportable Positive > Expected = Yes > Criteria: Isolation of Bordetella pertussis virus by culture methods in a clinical specimen
Isolation of Bordetella pertussis virus by culture methods in a clinical specimen
IF
1) Patient has lab result with (test name of [VS: Bordetella pertussis virus Organism Identification Test])
<Patient had lab test performed == RCKMSQ12>
and
2) [VS:Lab result value (Pertussis)]
<Lab Result == RCKMS1d>

Reporter Type: Lab Reporting

Offset Based? **Age Offset:** 21y

Date of Birth: 06/20/1995
Execution Date: 06/20/2016
Gender: Male (M)

Reportable?

Deployment of Reporting Specification to PH-DSS



- Scheduled or On-Demand
- Deployed via REST service invocation to OpenCDS
- Concepts and Mappings deployed to PH-DSS (value sets, individual code system codes, and concepts)
- Intermediate representation of the rules as HL7 CQL Expression Logical Model (ELM) format (XML)
 - o Standards-based, technology-agnostic, sharable representation
 - o Facilitates additional verification of the rules, race condition checks
- Final executable representation of rules as Drools

RCKMS Administrator-Only Configuration Functions



▼ CAT Admin
About
Manage Code Systems
Manage Concept Determination Methods
Manage Concepts
Manage Criteria Resources
Manage Data Models
Manage Data Templates
Manage Knowledge Modules
Manage Lists
Manage Properties
Manage Value Sets
Internal CAT User Editor
Internal CAT Security Editor

RCKMS Administrator-Only Criteria Authoring



Condition Criteria Editor - [Save Option 3]


ID: 5d434054f470cabfba4d01b398d2c1e1

Source Criteria Name: Isolation of virus or bacteria by any method in a clinical specimen

Label:


Criteria Predicate List (# of Results: 4)

Predicate

Patient has lab test performed of ==  Chlamydia trachomatis nucleic acid test (RCKMSQA9)

AND

▼ **Group 1** {

Lab Result Value ==  Positive qualitative lab result (RCKMS4a)

OR

Lab Result ==  Lab Result (Chlamydia trachomatis) (RCKMS5b)

OR

Interpretation ==  Abnormal Interpretation (RCKMS5a)

}